



Accurate Wiring and Component Analysis Anytime, Anywhere!

- ◆ *Portable Environmentally Sealed Packaging*
- ◆ *MIL-STD-810G, MIL-STD-461F, MIL-PRF-28800F Qualified*
- ◆ *Fully Programmable Measurement System up to 1500 vdc or 1000 vac*
- ◆ *512 Test Points with 256 Random Access (RAX) Points in Base Configuration*
- ◆ *Expandable to over 15,000 Test Points*
- ◆ *Remote Probe for isolated testing and troubleshooting*

Automatic Wire Test Set (AWTS) analyzers are DOD approved common support test sets for use at all levels of maintenance on all platforms. From established depots to remote deployments, this flexibility enables maintainers to choose where best to perform service and repair actions.

The AWTS -01 configuration (100000-01) is focused on supporting components tests which require AC Hipot. Electrical and electronic assemblies can now be tested in place to reduce maintenance costs.

Contact Us To Learn More!

ECLYPSE INTERNATIONAL

265 N. Joy Street Suite 150, Corona, CA 92879

Tel: (951) 371-8008 • Fax: (951) 371-8022

E-Mail: sales@eclipse.org

Web: <http://www.eclipse.org>



ECLYPSE INTERNATIONAL CORPORATION

SYSTEM SPECIFICATIONS

AWTS - 01

FEATURES

100000-01

Measurement System

Voltage Measurement Stimulus	0.25 to 500 VDC (+ or -)
Current Measurement Stimulus	0.005 to 1.0 Amps (+ or -)
Resistance Measurement	0 to 1000M Ohms
VI Measurement	0.001 to 1.0Amps (+ or -), 0 to 500 VDC (+ or -) <i>Used for:</i> Diode Forward Voltage / Reverse Leakage, Zener, Transistor Current Saturation, & more
DC HIPOT Measurement	0.5mA to 2.5mA (100 to 500 VDC)
DC Voltage Measurement	-200 to 200 VDC (up to 500 VDC non-switching)
AC Voltage Measurement	0.0 to 225 VAC (up to 350 VAC non-switching)
Capacitance Measurement	0 to 100 uF (extended ranges available)
Data Logging (Waveform Capture)	20kHz max sample rate, 2k buffer <i>Used for:</i> Pulse Width, Frequency, Event Timing, & more

Switching/Energization System

Test Address Points	512
RAX Energization Points	256 (2 Buses)
Voltage Energization	0-40 VDC @ 3 A (2 channels)

Standard Software

ELITE Operating System

- *Self-Program*
- *Menu-Driven Interface*
- *Self-Test (Diagnostics)*

IDE - Interface Device Editor
WTG - Wire Test Generator

Physical Characteristics

Input Power	115 / 230 VAC (auto-ranging), 50-400 Hz
Physical Dimensions (TCU)	14"H x 27.5"D x 21"W, @ 80.5 lbs.

Specifications subject to change without notice

Contact us today for additional information

ECLYPSE INTERNATIONAL CORPORATION

265 N. Joy Street Suite 150
Corona, California • 92879 • USA
Tel: (951) 371-8008 • Fax: (951) 371-8022
E-Mail: sales@eclipse.org
Web Site: www.eclipse.org